


Amendment to the Abstract:

The Abstract has been amended. A revised Abstract is attached.

Abstract

There are included a transmission modulator (103) for impulse-modulating the data to be transmitted, thereby producing a subcarrier; a subcarrier control section for controlling the subcarrier to be utilized for communication, depending on the amount and significance of information and on the propagation condition of communication; and an antenna section (101) for radiating the subcarrier signal. This structure allows selection of a subcarrier suitable for information to be transmitted and for propagation environment, and hence allows a communication to be performed which exhibits a high flexibility and a high noise immunity. Thus, there can be provided a communication apparatus that can perform a high-quality, high-stability communication exhibiting an improved interfering immunity and that performs a flexible impulse communication.

Respectfully submitted,


Lawrence E. Ashery, Reg. No. 34,515
Attorney for Applicants

LEA/dmw

Attachment: Abstract


Dated: October 18, 2004

P.O. Box 980
Valley Forge, PA 19482
(610) 407-0700

The Commissioner for Patents is hereby authorized to charge payment to Deposit Account No. 18-0350 of any fees associated with this communication.

Express Mail Number: EV 532 972 195 US
Date of Deposit: October 18, 2004

I hereby certify that this correspondence is being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to Mail Stop PCT, Commissioner for Patents, P.O. Box 1450, Alexandria, VA, 22313-1450.


Kathleen Libby

Abstract

There are included a transmission modulator for impulse-modulating the data to be transmitted, thereby producing a subcarrier; a subcarrier control section for controlling the subcarrier to be utilized for communication, depending on the amount and significance of information and on the propagation condition of communication; and an antenna section for radiating the subcarrier signal. This structure allows selection of a subcarrier suitable for information to be transmitted and for propagation environment, and hence allows a communication to be performed which exhibits a high flexibility and a high noise immunity. Thus, there can be provided a communication apparatus that can perform a high-quality, high-stability communication exhibiting an improved interfering immunity and that performs a flexible impulse communication.